

Touch Lamina



An alternative way for you to control any device connected to the SiluxControl® network. You can replace it or use it as an addition to your current switches. With the added bonus of being wireless, you can easily place it where it is most convenient.



Touch Lamina Specifications

General

Dimensions (L x W x H)	70 x 120 13.5mm (other sizes coming soon)
Installation	Refer to manual
Operating Temperature/Humidity	0°C~40°C 10%~90% RH (Non-Condensing)
Storage Temperature/Humidity	-10°C ~70°C 5%~90% RH (Non-Condensing)
Warranty	1 Year
Certification	CE, FCC
Environmental Directive	RoHS

Outline

Input	3V (2 x CR2032 batteries)
Pairing	Silux Control App hardware teach
Direct Pairing	Can be directly paired with devices you wish to control. With direct pairing you will not be able to use the Silux Control Network.
Features	<ul style="list-style-type: none">• Comes in a 2 Button, 4 Button or 6 Button touch plate.• Program any button to switch devices on/off such as: Air conditioning, lighting, plug points and swimming pool pumps etc.• Can be programmed to be used without the need of IntelliHub
Dimmable option	if applicable

Communications

RF Network	Silux RF proprietary
RF Range	50m open air & meshing up to 1km
RF Encryption	Silux RF proprietary meshing
Radio Frequency	868MHZ Adjustable frequency to meet different countries legislations

System

Language	English, others coming soon
OS	Android 4.0+, iOS 8.0+