

Collector

Dry Contact



Product Overview

The Collector® Dry Contact joins into your existing electrical infrastructure of many various types of devices, that require an isolated output connection, without the need for any extra wiring. It has the ability to control any devices that may require isolated relay control.

Features:

- Output: Control latch output with app
- Latch timing control
- Control: Set normally open/normally closed via the Silux Control® app software
- Connect to motorized doors/gates, alarm panels and many other applications

Specifications

Input	12V/24V DC 3Amp Fused
Output	Isolated output Normally open/normally closed 12V AC/DC-230V/AC 8Amps
Operating Temperature	0 °C ~ 40 °C 10% ~90% RH
Storage Temperature	-10 °C ~ -70 °C 5% ~90% RH
Pairing	<ul style="list-style-type: none"> • Silux Control® network • Direct connect • Software teach available
Network	Silux Control® RF proprietary encrypted
RF Range	50m open air & meshing up to 1km
Encryption	Silux Control® RF proprietary meshing
Language	English, others coming soon
OS	Android 4.0+, IOS 8.0+, Windows 7+
App Software	Silux Control® can be integrated with other automation features of Silux Control®

Works cooperatively with:

Product dimensions:
38.5 x 92 x 22.5mm

CE **RoHS**
Compliant